

# 2025 Sportsman Touring 570 EPS Stealth Gray



## Key Specifications

<b>44</b>	<b>48"</b>	<b>11.5"</b>
<b>HORSEPOWER</b>	<b>VEHICLE WIDTH</b>	<b>GROUND CLEARANCE</b>

## ENGINE & DRIVETRAIN

<b>Active Descent Control</b>	Not Equipped
<b>Cooling</b>	Liquid
<b>Cylinders Displacement</b>	567cc
<b>Drive System Type</b>	One Touch On-Demand AWD/2WD
<b>Electronic Power Steering</b>	Multi Select EPS
<b>Engine Braking System (EBS)</b>	Not Equipped
<b>Engine Type</b>	ProStar 4-Stroke DOHC Single Cylinder
<b>Fuel System/Battery</b>	Electronic Fuel Injection / 340 CCA
<b>Horsepower</b>	44 HP
<b>Transmission/Final Drive</b>	Automatic PVT P/R/N/L/H In-line Shifting

## DIMENSIONS

<b>Bed Box Dimensions (L x W x H)</b>	N/A
<b>Estimated Dry Weight</b>	800 lbs (363 kg)
<b>Front/Rear Rack</b>	90 lb/180 lb (40.8 kg/82 kg)
<b>Fuel Capacity</b>	6.75 gal (25.5 L)
<b>Ground Clearance</b>	11.5 in (29 cm)
<b>Hitch Tow Rating</b>	1,350 lb (612 kg)
<b>Hitch Type</b>	Standard 1.25 in (3.2 cm) Receiver
<b>Overall Vehicle Size (L x W x H)</b>	89 x 48 x 59 in (226 x 121.2 x 150 cm)
<b>Payload Capacity</b>	485 lb (220 kg)

<b>Person Capacity</b>	2
<b>Seat Height</b>	35.25 (89.5 cm)
<b>Wheelbase</b>	56 in (143.2 cm)

## BRAKES

<b>Front/Rear Brakes</b>	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
<b>Parking Brake</b>	Park In-Transmission / Lockable Hand Lever

## ADDITIONAL SPECIFICATIONS

<b>Cargo system</b>	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage, 6 Gal (23 L) Rear Storage, Toolless Removable Passenger Seat
<b>Instrumentation</b>	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet
<b>Lighting</b>	50w High Beam, Dual 50w Low Beam Headlights, Dual Brake Lights/Tail Lights
<b>Other Standard Features</b>	Front Rack Extender, Front A-Arm Guards
<b>RIDE COMMAND+</b>	Available as Accessory

## TIRES / WHEELS

<b>Front Tires</b>	25x8-12 P373; 6 PLY
<b>Rear Tires</b>	25 x 10-12 P373; 6 PLY
<b>Wheels</b>	12 in. (30.5 cm) Steel

## SUSPENSION

<b>Front Suspension</b>	Sealed MacPherson Strut With 8.2 in (20.8 cm) Travel
<b>Rear Suspension</b>	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel