2025 Sportsman 450 H.O. EPS Sage Green



Key Specifications			
33	48"	11.5"	
HP	WIDTH	GROUND CLEARANCE	

ENGINE & DRIVETRAIN

Active Descent Control	Not Equipped
Cooling	Liquid
Cylinders Displacement	499cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	Prostar 4-Stroke SOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	33 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	726 lbs (329 kg)
Front/Rear Rack	90 lb /180 lb (40.8 kg /81.6 kg)
Fuel Capacity	4.5 gal (17.0 L)
Ground Clearance	11.5 in (29 cm)
Hitch Tow Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)
Payload Capacity	485 lb (220 kg)
Person Capacity	1

MacGyver Solutions Inc 217-254-3620

cage: 7JP09 duns: 080019034 UEI# JKVNT2ZWLA44

33.25 in (84.5 cm)

50.5 in (128.3 cm)

BRAKES

Seat Height

Wheelbase

Front/Rear Brakes	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

ADDITIONAL SPECIFICATIONS

Cargo system	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage
Electronic Power Steering	Multi Select EPS
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light
Lighting	Halogen Pod & Bumper Lights, Triple 50w High Beams, Dual 50w Low Beams, Dual LED Brake Light/Taillight
Other Standard Features	Front Rack Extender, Rear Rack Extender, 12 Volt Power Plug, Pre- Wired for Hand & Thumb Warmers, In Pod Battery Charger, Winch Mount Included

TIRES / WHEELS

Front Tires	25x8-12 P373; 6 PLY
Rear Tires	25x10-12 P373; 6 PLY
Wheels	12 in. (30.5 cm) Steel

SUSPENSION

Front Suspension	Sealed MacPherson Strut With 8.2 in (20.8 cm) Travel
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel