

# 2025 Sportsman 570 EPS Sage Green



## Key Specifications

<b>44</b>	<b>48"</b>	<b>11.5"</b>
HP	WIDTH	GROUND CLEARANCE

## ENGINE & DRIVETRAIN

Active Descent Control	Not Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

## DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	760 lb (345 kg)
Front/Rear Rack	90 lb /180 lb (40.8 kg /81.6 kg)
Fuel Capacity	4.5 gal (17.0 L)
Ground Clearance	11.5 in (29 cm)
Hitch Tow Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	86 x 48 x 48 in (218.4 x 121.9 x 121.9 cm)
Payload Capacity	485 lb (220 kg)
Person Capacity	1
Seat Height	33.25 in (84.5 cm)

<b>Wheelbase</b>	50.5 in (128.3 cm)
------------------	--------------------

## BRAKES

<b>Front/Rear Brakes</b>	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
<b>Parking Brake</b>	Park In-Transmission / Lockable Hand Lever

## ADDITIONAL SPECIFICATIONS

<b>Cargo system</b>	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage
<b>Electronic Power Steering</b>	Multi Select EPS
<b>Instrumentation</b>	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light
<b>Lighting</b>	Halogen Pod & Bumper Lights, Triple 50w High Beams, Dual 50w Low Beams, Dual LED Brake Light/Taillight
<b>Other Standard Features</b>	Front Trail Bumper, Front Rack Extender, Rear Rack Extender, 12 Volt Power Plug, Pre-Wired for Hand & Thumb Warmers, In Pod Battery Charger, Winch Mount Included, Front A-Arm Guards

## TIRES / WHEELS

<b>Front Tires</b>	25x8-12 P373; 6 PLY
<b>Rear Tires</b>	25x10-12 P373; 6 PLY
<b>Wheels</b>	12 in. (30.5 cm) Steel

## SUSPENSION

<b>Front Suspension</b>	Sealed MacPherson Strut With 8.2 in (20.8 cm) Travel
<b>Rear Suspension</b>	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel