2025 Sportsman 570 Hunt Edition Polaris Pursuit Camo



Key Specifications		
44	48"	11.5"
HP	WIDTH	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Active Descent Control	Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	866 lb (392.8 kg)
Front/Rear Rack	90 lb /180 lb (40.8 kg /81.6 kg)
Fuel Capacity	4.5 gal (17.0 L)
Ground Clearance	11.5 in (29 cm)
Hitch Tow Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)
Payload Capacity	485 lb (220 kg)
Person Capacity	1

MacGyver Solutions Inc 217-254-3620

cage: 7JP09 duns: 080019034 UEI# JKVNT2ZWLA44

Seat Height	33.25 in (84.5 cm)
Wheelbase	50.5 in (128.3 cm)

BRAKES

Front/Rear Brakes	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

ADDITIONAL SPECIFICATIONS

Cargo system	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage, 6 Gal (27.3L) Rear Dry Storage
Electronic Power Steering	Multi Select EPS
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light
Lighting	High Output LED POD, High Output LED Bumper Lights, Dual LED Brake lights/Taillights
Other Standard Features	Front and Rear A-Arm Guards, Front Trail Bumper, Rear Trail Bumper, Front Rack Extender, Rear Rack Extender, 2,500 lb Polaris Winch, Dipped Camo Plastics, Upgraded Wheels & PXT Tires, Kolpin Gun Scabbard & Mount, Kolpin Ratchet Claws, Hand & Thumb Warmers, 12 Volt Power Plug, In Pod Battery Charger

TIRES / WHEELS

Front Tires	26 x 8-14; PXT
Rear Tires	26 x 10-14; PXT
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Sealed Arched Dual A-Arm with 8.9 in (22.6 cm) Travel
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel