2025 Sportsman 570 Ultimate Turbo Silver



Key Specifications

44

48"

11.5"

HP WIDTH

GROUND CLEARANCE

ENGINE & DRIVETRAIN

Active Descent Control	Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	883 lbs (400 kg)
Front/Rear Rack	90 lb /180 lb (40.8 kg /81.6 kg)
Fuel Capacity	4.5 gal (17.0 L)
Ground Clearance	11.5 in (29 cm)
Hitch Tow Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)
Payload Capacity	485 lb (220 kg)
Person Capacity	1

Seat Height	33.25 in (84.5 cm)
Wheelbase	50.5 in (128.3 cm)

BRAKES

Front/Rear Brakes	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

ADDITIONAL SPECIFICATIONS

Cargo system	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage, 6 Gal (27.3L) Rear Dry Storage
Electronic Power Steering	Multi Select EPS
Instrumentation	7" Glove Touch Display, All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Text and Call Notifications
Lighting	High Output LED POD, High Output LED Bumper Lights, Dual LED Brake lights/Taillights
Other Standard Features	7" Glove Touch Display, Plow Mode, Group Ride, GPS Navigation, Bluetooth, 3,500 lb. Polaris HD Winch with Auto Stop and Synthetic Rope, Front Trail Bumper, Front and Rear Rack Extenders, Painted Plastics, Painted Springs, In Pod USB Charger, PIN Activated Secrity System (P.A.S.S.), Front and Rear A-Arm Guards

TIRES / WHEELS

Front Tires	26 x 8-14; DURO
Rear Tires	26 x 10-14; DURO
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Sealed Arched Dual A-Arm with 8.9 in (22.6 cm) Travel
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel