

2025 Sportsman Touring 570 Ultimate Granite Gray



Key Specifications

44

HORSEPOWER

48"

VEHICLE WIDTH

11.5"

GROUND CLEARANCE

ENGINE & DRIVETRAIN

Active Descent Control	Equipped
Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	One Touch On-Demand AWD/2WD
Electronic Power Steering	Multi Select EPS
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke DOHC Single Cylinder
Fuel System/Battery	Electronic Fuel Injection / 340 CCA
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	911 lbs (413 kg)
Front/Rear Rack	90 lb/180 lb (40.8 kg/82 kg)
Fuel Capacity	6.75 gal (25.5 L)
Ground Clearance	11.5 in (29 cm)
Hitch Tow Rating	1,350 lb (612 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	91 x 48 x 59 in (231.1 x 121.2 x 150 cm)
Payload Capacity	485 lb (220 kg)

Person Capacity	2
Seat Height	35.75 in (90.8 cm)
Wheelbase	56 in (143.2 cm)

BRAKES

Front/Rear Brakes	Single Lever 3-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

ADDITIONAL SPECIFICATIONS

Cargo system	Lock & Ride Compatible 5 Gal (18.9L) Front Dry Storage, 6 Gal (23 L) Rear Storage, Toolless Removable Passenger Seat
Instrumentation	7" Glove-Touch Display Powered by RIDE COMMAND, All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Text and Call Notifications
Lighting	High Output LED POD High Beam, High Output LED Low Beam Headlights, Dual LED Brake Lights/Tail Lights
Other Standard Features	Front and Rear A-Arm Guards, Front Trail Bumper, 3,500 lb Polaris HD Winch, Front and Rear Rack Extender, Painted Plastics, PIN Activated Security System (P.A.S.S.), USB Data/Charging Port
RIDE COMMAND+	Available as Accessory

TIRES / WHEELS

Front Tires	26 x 8-14; DURO
Rear Tires	26 x 10-14; DURO
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Sealed Arched Dual A-Arm with 8.9 in (22.6 cm) Travel
Rear Suspension	Sealed Dual A-Arm, IRS 9.5 in (24.1 cm) Travel