# 2025 Sportsman XP 1000 S Lava Orange Metallic



# **Key Specifications**

89 55" 14.5"

HP WIDTH GROUND CLEARANCE

### **ENGINE & DRIVETRAIN**

Active Descent Control	Equipped
Cooling	Liquid
Cylinders Displacement	2/952cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke SOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection / 400 CCA
Horsepower	89 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

## **DIMENSIONS**

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	970 lb (440 kg)
Front/Rear Rack	200 lb / 300 lb (91 kg / 136 kg)
Fuel Capacity	5.25 gal (19.9 L)
Ground Clearance	14.5 in (36.8 cm)
Hitch Towing Rating	1,750 lb (794 kg)
Hitch Type	Standard 2 in (5.08 cm) Receiver
Overall Vehicle Size (L x W x H)	82.5 x 55 x 49.5 in (209.5 x 140 x 125.7 cm)
Payload Capacity	715 lbs (324 kg)
Person Capacity	1

Seat Height	37 in (94 cm)
Wheelbase	56.8 in (144.27 cm)

#### **BRAKES**

Front/Rear Brakes	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

## **ADDITIONAL SPECIFICATIONS**

Cargo system	Lock & Ride 4 Gal (15L) Front, 2 Gal (8L) Rear
Electronic Power Steering	Multi Select EPS
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet
Lighting	High Output LED POD, High Output LED Bumper Lights, Dual LED Brake lights/Taillights
Other Standard Features	Walker Evans 3-Way Adjustable Shocks, Front Bumper, Rear Bumper, 3,500 lb. Winch, Cut and Sew Seat, Painted Plastics, In Pod Battery Charge Port, PIN Activated Secrity System (P.A.S.S.), Fender Flares, 6 Moveable Tie-Down Points

## **TIRES / WHEELS**

Front Tires	27 X 9-14 DURO PowerGrip V2
Rear Tires	27 X 11-14 DURO PowerGrip V2
Wheels	14 in. (35.6 cm) Aluminum

### **SUSPENSION**

Front Suspension	Sealed High Clearance Arched Dual A-Arm 11.6 in (29.5 cm) Travel
Rear Suspension	Sealed Dual A-Arms Rolled IRS, 14 in (35.6 cm) Travel