

2025 Sportsman XP 1000 Ultimate Turbo Silver



Key Specifications

90

HP

47.6"

WIDTH

12"

GROUND CLEARANCE

ENGINE & DRIVETRAIN

Active Descent Control	Equipped
Cooling	Liquid
Cylinders Displacement	2 / 952cc
Drive System Type	One Touch On-Demand AWD/2WD
Engine Braking System (EBS)	Equipped
Engine Type	ProStar 4-Stroke SOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection / 400 CCA
Horsepower	90 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H In-line Shifting

DIMENSIONS

Bed Box Dimensions (L x W x H)	N/A
Estimated Dry Weight	867 lbs (393 kg)
Front/Rear Rack	120 lb (55 kg)/240 lb (110 kg)
Fuel Capacity	5.25 gal (19.9 L)
Ground Clearance	12 in (30.5 cm)
Hitch Tow Rating	1,500 lb (680 kg)
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Overall Vehicle Size (L x W x H)	83.25 x 47.6 x 50.75 in (211.4 x 120.9 x 128.9 cm)
Payload Capacity	575 lb (261 kg)
Person Capacity	1

Seat Height	37 in (94 cm)
Wheelbase	53 in (134.6 cm)

BRAKES

Front/Rear Brakes	Single Lever 4-Wheel Hydraulic Disc with Hydraulic Rear Foot Brake
Parking Brake	Park In-Transmission / Lockable Hand Lever

ADDITIONAL SPECIFICATIONS

Cargo system	Lock & Ride, 4 Gal (15 L) Front Dry Storage 2 Gal (8 L) Rear Storage
Electronic Power Steering	Multi Select EPS
Instrumentation	7" Glove Touch Display, All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Text and Call Notifications
Lighting	High Output LED POD, High Output LED Bumper Lights, Dual LED Brake lights/Taillights
Other Standard Features	7" Glove Touch Display, Plow Mode, Group Ride, GPS Navigation, Bluetooth, Ride Command+ Technology, 3,500 lb. Polaris HD Winch with Auto Stop and Synthetic Rope, Front Ultimate Series Bumper, Cut and Sew Seat, In Pod Battery Charge Port, Painted Plastics, Painted Springs, In Pod USB Charger, PIN Activated Security System (P.A.S.S.), Fender Flares, 6 Moveable Tie-Down Points

TIRES / WHEELS

Front Tires	27 X 9-14 DURO
Rear Tires	27 X 11-14 DURO
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Sealed High Clearance Arched Dual A-Arm 9" (22.9 cm) Travel
Rear Suspension	Sealed High Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel