

2025 RANGER CREW SP 570 Premium Zenith Blue



Key Specifications

44

HP

56"

WIDTH

11"

GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Single Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	33.3 x 48.7 x 12.3 in (84.6 x 123.7 x 31.2 cm)
Box Capacity	500 lb (226.8 kg)
Estimated Dry Weight	1,550 lbs. (703 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	11 in (27.9 cm)
GVW	2,700 lbs (1,225 kg)
Hitch Towing Rating	1,500 lb (680 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	144 x 56 x 74 in. (365.8 x 142.2 x 188 cm)
Payload Capacity	1,100 lbs. (499 kg)
Person Capacity	4

Wheelbase	105 in (266.7 cm)
------------------	-------------------

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Zenith Blue
Electronic Power Steering	Standard
Gauge	B1
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	High/Low Beam LED Headlights LED Taillamps
Other Standard Features	Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 575 CCA Battery, 660W Charging System (Stator), 48.4 Gal. Onboard Storage with Enclosed Dash Bins and Integrated Cell-phone Holder, Sealed Suspension Bushings and Wheel Bearings, Full Coverage Steel Front Bumper with Integrated Winch and Plow Mounts, Full Coverage Skid Plate, Premium Body Panels, Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), USB Charging Port, Front Stabilizer Bar, Rear Wheel Liners
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	25 x 8-12; Carlstar 489
Rear Tires	25 x 10-12; Carlstar 489
Wheels	Aluminum

SUSPENSION

Front Suspension	MacPherson Strut 9 in (22.9 cm) Travel
Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
Turning Radius	16.3 ft (497.8 cm)