

2025 RANGER CREW SP 570 NorthStar Edition Zenith Blue



Key Specifications

44 HP	58" WIDTH	10.3" GROUND CLEARANCE
-----------------	---------------------	----------------------------------

ENGINE & DRIVETRAIN

Cooling	Liquid
Displacement	567cc
Drive System Type	On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Single Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	33.3 x 48.7 x 12.3 in (84.6 x 123.7 x 31.2 cm)
Box Capacity	500 lb (226.8 kg)
Estimated Dry Weight	1,904 lbs (864 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	10.3 in (26.1 cm)
GVW	2,700 lbs (1,225 kg)
Hitch Towing Rating	1,500 lb (680 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	144 x 58 x 74 in. (365.8 x 147.3 x 188 cm)
Payload Capacity	750 lbs. (340 kg)
Person Capacity	4

Water Forging Height	Equal to the Floorboards
Wheelbase	105 in (2,667 mm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Zenith Blue
Electronic Power Steering	Standard
Gauge	B1
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	High/Low Beam LED Headlights LED Taillamps
Other Standard Features	Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 575 CCA Battery, 660W Charging System (Stator), 48.4 Gal. Onboard Storage with Enclosed Dash Bins and Integrated Cell-phone Holder, Sealed Suspension Bushings and Wheel Bearings, Full Coverage Steel Front Bumper with Integrated Winch and Plow Mounts, Full Coverage Skid Plate, Premium Body Panels, Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), Polaris HD 3,500 Lb. Synthetic Rope Winch with Autostop and In-Dash Switch, Premium Pro-Shield Cab, Doors with Crank Windows, Integrated Door Storage, Fixed Glass Windshield with Wiper and Washer Fluid, Rear Glass Panel, Factory Installed Heat with Defrost, Upper and Lower Dash Vents and Variable Fan Speed, USB Charging Port, Front Stabilizer Bar, Rear Wheel Liners,, NorthStar Badging
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	25 x 8-12; Pro Armor X Terrain
Rear Tires	25 x 10-12; Pro Armor X Terrain
Wheels	Aluminum

SUSPENSION

Front Suspension	MacPherson Strut 9 in (22.9 cm) Travel
Rear Suspension	Dual A-Arm 10.0 in (25.4 cm) Travel
Turning Radius	16.3 ft (498 cm)