2025 RANGER XP 1000 Premium Stealth Gray



Key Specifications		
82	62.5"	14"
HP	WIDTH	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 4-Stroke Twin Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	82 HP
Transmission/Final Drive	Gen 2 Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93 x 138 x 32 cm)
Box Capacity	1000 lbs(454 kg)CA Models: 600 lbs(272 kg)
Estimated Dry Weight	1,684 lb (764 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	14 in (36 cm)
GVW	3600 lbs(1633 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 79.5 in. (305 x 158 x 201 cm)
Payload Capacity	1500 lbs (680 kg) CA Models: 1100 lbs (499 kg)
Person Capacity	3

MacGyver Solutions Inc 217-254-3620

cage: 7JP09 duns: 080019034 UEI# JKVNT2ZWLA44

Water Fording Height	Equal to the Floorboards
Wheelbase	81 in (206 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Standard
Audio System	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Stealth Gray
Electronic Power Steering	High Output EPS
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet, USB Charge Port, Automatic Speed Limiting in 2 mph increments starting at 16 mph to max speed.
Lighting	Dual LED Headlights, 1250Im Low Beam, 2300Im High Beam, Dual LED Tail Lights
Other Standard Features	Front Bumper with Integrated Winch, Plow & LED Mounts, Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Polaris HD 4500 lb Synthetic Rope Winch with Autostop and Wireless Remote, Factory-Installed Poly Sport Roof, Single Latch Cab Nets, Polaris Pulse Electrical System (6 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet, USB Outlet
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

TIRES / WHEELS

Rear Tires	29 x 11-14; PRO ARMOR X-TERRAIN
Tire Ply Rating	8-Ply Rated
Wheels	Aluminum

SUSPENSION

Front Suspension	Dual A-Arm, 10 in (25.4 cm)
Rear Suspension	Dual A-Arm IRS, 10 in (25.4 cm)
Turning Radius	13 ft. (4.0 m)