2025 RANGER CREW XP 1000 Premium Onyx Black



ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 4-Stroke Twin Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	82 HP
Transmission/Final Drive	Gen 2 Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93 x 138 x 32 cm)
Box Capacity	1000 lbs (454 kg) CA Models: 600 lbs (272 kg)
Estimated Dry Weight	1,953 lbs (886 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	14 in (36 cm)
GVW	3750 lbs (1701 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	152 x 62.5 x 79.5 in. (386 x 158 x 201 cm)
Payload Capacity	1600 lbs (726 kg) CA Models: 1350 lbs (612 kg)
Person Capacity	6

Wa	ater Fording Height	Equal to the Floorboards
Wh	heelbase	113 in (287 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Standard
Audio System	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Onyx Black
Electronic Power Steering	High Output EPS
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 2 DC Outlets, USB Charge Port, Automatic Speed Limiting in 2 mph increments starting at 16 mph to max speed.
Lighting	Dual LED Headlights, 1250lm Low Beam, 2300lm High Beam, Dual LED Tail Lights
Other Standard Features	Front Bumper with Integrated Winch, Plow & LED Mounts, Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Polaris HD 4500 lb Synthetic Rope Winch with Autostop and Wireless Remote, Factory-Installed Poly Sport Roof, Single Latch Cab Nets, Polaris Pulse Electrical System (6 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet, USB Outlet
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	29 x 9-14; PRO ARMOR X-TERRAIN
Rear Tires	29 x 11-14; PRO ARMOR X-TERRAIN
Tire Ply Rating	8-Ply Rated
Wheels	Aluminum

SUSPENSION

Front Suspension	Dual A-Arm, 10 in (25.4 cm)
Rear Suspension	Dual A-Arm, IRS 11 in (27.9 cm) Travel