# 2025 RANGER CREW 1000 Premium White Lightning



# **Key Specifications**

61

62.5"

**WIDTH** 

12"

**GROUND CLEARANCE** 

#### **ENGINE & DRIVETRAIN**

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder SOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	61 HP
Transmission/Final Drive	Gen 2 Automatic PVT H/L/N/R/P; Shaft

# **DIMENSIONS**

Bed Box Dimensions (L x W x H)	36.75 x 54 x 11.5 in (93.3 x 137 x 29 cm)
Box Capacity	1000 lbs (454 kg) CA Models: 600 lbs (272 kg)
Estimated Dry Weight	1853 lbs (841 kg)
Fuel Capacity	11.35 gal (43 L)
Ground Clearance	12.5 in (31.75 cm)
GVW	3750 lbs (1701 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	152 x 62.5 x 78 in (386 x 159 x 198 cm)
Payload Capacity	1750 lbs (794 kg) CA Models: 1350 lbs (612 kg)
Person Capacity	6

'	Water Fording Height	Equal to the Floorboards
,	Wheelbase	113 in (287 cm)

#### **BRAKES**

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

# **ADDITIONAL SPECIFICATIONS**

Adjustable Driver Seat	Standard
Audio System	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	White Lightning
Electronic Power Steering	High Output EPS
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	Dual LED Headlights, 600lm Low Beam, 1000lm High Beam, Dual LED Tail Lights
Other Standard Features	Polaris HD 4500 lb Synthetic Rope Winch with Autostop and Wireless Remote, Factory-Installed Poly Sport Roof, Premium Cut & Sew Bench Seats, Front Bumper with Integrated Plow & Winch Mounts, Single Latch Cab Nets, Polaris Pulse Electrical System (3 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

# **TIRES / WHEELS**

Front Tires	26 x 9-12; PXT 2.0
Rear Tires	26 x 11-12; PXT 2.0
Wheels	Aluminum Black Xcelerator 2.0

# **SUSPENSION**

Front Suspension	Dual A-Arm, 10 in (25.4 cm)
Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
Turning Radius	17 ft (5.2 m)