

## 2025 RANGER 1000 Sage Green



### Key Specifications

**61**  
HP

**62.5"**  
WIDTH

**12"**  
GROUND CLEARANCE

## ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder SOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	61 HP
Transmission/Final Drive	Gen 2 Automatic PVT H/L/N/R/P; Shaft

## DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54 x 11.5 in (93.3 x 137 x 29 cm)
Box Capacity	1000 lbs (454 kg) CA Models: 600 lbs (272 kg)
Dry Weight	1,437 lb (652 kg)
Front/Rear Rack	N/A
Fuel Capacity	11.35 gal (43 L)
Ground Clearance	12 in (30.5 cm)
GVW	3600 lbs (1633 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 76 in (305 x 159 x 193 cm)
Payload Capacity	1500 lbs (680 kg) CA Models: 1100 lbs (499 kg)
Person Capacity	3

<b>Water Fording Height</b>	Equal to the Floorboards
<b>Wheelbase</b>	81 in (206 cm)

## BRAKES

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
<b>Parking Brake</b>	Park In-Transmission

## ADDITIONAL SPECIFICATIONS

<b>Adjustable Driver Seat</b>	Not Equipped
<b>Audio System</b>	Not Equipped
<b>Cargo System</b>	Lock & Ride®
<b>Color / Graphics</b>	Sage Green
<b>Electronic Power Steering</b>	Not Equipped
<b>Instrumentation</b>	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
<b>Lighting</b>	Halogen Headlights, 55W Low Beam, 60W High Beam, Dual LED Tail Lights
<b>Other Standard Features</b>	Single Latch Cab Nets, Polaris Pulse Electrical System (3 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet
<b>RIDE COMMAND+</b>	Available as Accessory
<b>Tilt Steering</b>	Standard

## TIRES / WHEELS

<b>Front Tires</b>	25 x 10-12; CarlStar 489
<b>Rear Tires</b>	25 x 11-12; CarlStar 489
<b>Wheels</b>	Stamped Steel

## SUSPENSION

<b>Front Suspension</b>	Dual A-Arm, 10 in (25.4 cm)
<b>Rear Suspension</b>	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
<b>Turning Radius</b>	13.3 ft. (4.1 m)