

2025 RANGER 1000 EPS Sage Green



Key Specifications

61
HP

62.5"
WIDTH

12"
GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder SOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	61 HP
Transmission/Final Drive	Gen 2 Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54 x 11.5 in (93.3 x 137 x 29 cm)
Box Capacity	1000 lbs (454 kg) CA Models: 600 lbs (272 kg)
Estimated Dry Weight	1,485 lb (674 kg)
Fuel Capacity	11.35 gal (43 L)
Ground Clearance	12 in (30.5 cm)
GVW	3600 lbs (1633 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 76 in (305 x 159 x 193 cm)
Payload Capacity	1500 lbs (680 kg) CA Models: 1100 lbs (499 kg)
Person Capacity	3
Water Fording Height	Equal to the Floorboards

Wheelbase	81 in (206 cm)
------------------	----------------

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Not Equipped
Audio System	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Sage Green
Electronic Power Steering	High Output EPS
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	Halogen Headlights, 55W Low Beam, 60W High Beam, Dual LED Tail Lights
Other Standard Features	Front Bumper with Integrated Plow & Winch Mounts, Single Latch Cab Nets, Polaris Pulse Electrical System (3 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet
RIDE COMMAND+	Available as Accessory
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	25 x 10-12; Carlstar 489
Rear Tires	25 x 11-12; Carlstar 489
Wheels	Stamped Steel

SUSPENSION

Front Suspension	Dual A-Arm, 10 in (25.4 cm)
Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
Turning Radius	13.3 ft. (4.1 m)