

2025 RZR Trail S 1000 Ultimate Sand Dune



Key Specifications

100
HP

60"
WIDTH

12.5"
GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	100 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	20.7 x 37 x 7.9 in (52.5 x 94 x 20 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	1360 lb (616.9 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	12.5 in (31.8 cm)
Hitch Towing Rating	1500 lb (680.4 kg)
Overall Vehicle Size (L x W x H)	110.9 x 60 x 69.3 in (282 x 152.4 x 176 cm)
Payload Capacity	740 lb (335.7 kg)
Person Capacity	2
Wheelbase	79 in (200.7 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Audio	Premium Rockford Fosgate® Stage 2 Audio
Cargo System	Lock & Ride®
Doors	Full Doors
Electronic Power Steering	Yes
Hitch Type	Standard 1.25 in (3.2 cm) Receiver
Instrumentation	RIDE COMMAND 7" Glove-Touch Display: Built-In GPS, *Group Ride (Cell and Non-Cell Communications), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio Capable, In-Vehicle Communications Capable With Optional Sena Headsets Dual-Sweep Analog Dials with 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet + 12V Power Plug
Lighting	Signature White LED Low/High with Accent Lights & Red LED Tail/Brake Lights
Other Standard Features	Poly Roof, Rear Camera, Adjustable Tilt Steering, Turf Mode, Polaris P.A.S.S.
Seat Type	Bolstered Bucket Seats with Toolless Driver Seat Slider and Standard Passenger Seat Slider (Tool Required for Adjustment on Passenger Seat)

TIRES / WHEELS

Front Tires	27 x 9-12
Rear Tires	27 x 11-12
Wheels	Cast Aluminum

SUSPENSION

Electronic Suspension Control System	Not Equipped
Front Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 12.25 in (31.1 cm) Wheel Travel
Rear Shocks	2 in Walker Evans Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Dual A-Arm with Stabilizer Bar and 13.2 in (33.5 cm) Wheel Travel