2025 RZR XP 1000 Sport Storm Gray



Key Specifications

114 64" 14"

HP WIDTH GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 1000 4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	114 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	1567 lbs (710 kg)
Fuel Capacity	9.5 gal (36 L)
Ground Clearance	14 in (35.6 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	119.5 x 64 x71.1 in (303.5 x 162.6 x 180.6 cm)
Payload Capacity	740 lb (336 kg)
Person Capacity	2
Wheelbase	90 in (228.6 cm)

BRAKES

Parking Brake	Rear Calipers Park In-Transmission	
Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers and Single-Bore	

ADDITIONAL SPECIFICATIONS

Audio	Not Equipped, Accessory Options Available
Cargo System	Lock & Ride®
Doors	Full Doors
Electronic Power Steering	Standard with Quick Turn Rack
Hitch Type	Not Equipped
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	LED Head Lights & Tail Lights Illuminated In-Cab Controls
Other Standard Features	Color Matched Seats Programmable Speed Limiting PIN Enabled Engine Start Security 660-W Charging System @ 3,000 RPM 6-Position PULSE Bar Front Tow Loop Front Bumper Passenger Grab Handle with Integrated Lug Nut Hex Wrench
RIDE COMMAND+	Available as Accessory
Seat Type	Bolstered Bucket Seats with Driver Seat Slider Retractable 3-Point Seat Belts

TIRES / WHEELS

Front Tires	29 x 9-14; Radial Tire
Rear Tires	29 x 11-14; Radial Tire
Tilt Steering	Standard Tilt
Wheels	Cast Aluminum

SUSPENSION

Electronic Suspension Control System	Not Equipped
Front Shocks	2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
Rear Shocks	2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel