2025 RZR XP 1000 Ultimate Storm Gray



Key Specifications

114 HP 64"

WIDTH

14.5"

GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Odding	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 1000 4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	114 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	1650 lbs (748 kg)
Fuel Capacity	9.5 gal (36 L)
Ground Clearance	14.5 in (36.8 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	120 x 64 x 74 in (304.8 x 162.6 x 188 cm)
Payload Capacity	740 lb (336 kg)
Wheelbase	90 in (228.6 cm)

BRAKES

Front/Rear Brakes

	4-Wheel Hydraulic Disc with Dual-Bore Front and Single Bore Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Rockford Fosgate® Stage 3 Audio (Including 2 Front & 2 Rear Co-axial Speakers and External 400W Amp)
Lock & Ride®
Full Doors
Standard with Quick Turn Rack
Not Equipped
7" Display Powered by RIDE COMMAND: Rear View Camera, Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp
LED Head Lights & Tail Lights Illuminated In-Cab Controls
Integrated 4,500 lb Winch Color Matched Seats Programmable Speed Limiting PIN Enabled Engine Start Security Premium Painted Bumper and Springs 900-W Charging System @ 3,000 RPM 6-Position PULSE Bar Poly Sport Roof Front Tow Loop Front Bumper with Integrated Tie Down Loop Passenger Grab Handle with Integrated Lug Nut Hex Wrench Driver and Passenger Dash Storage Bins
Available as Accessory

TIRES / WHEELS

Front Tires	30 x 10-14 Radial Tire
Rear Tires	30 x 10-14 Radial Tire
Tilt Steering	Standard Tilt
Wheels	Cast Aluminum

SUSPENSION

Electronic Suspension Control System	Not Equipped
Front Shocks	2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 20.5 in (52.07 cm) *Usable Travel, 16 in (40.6 cm) of Wheel Travel
Rear Shocks	2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers

MacGyver Solutions Inc 217-254-3620

cage: 7JP09 duns: 080019034 UEI# JKVNT2ZWLA44

Rear Suspension

Trailing Arm with Stabilizer Bar and 20.5 in (52.07 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel