

## 2025 RZR XP 4 1000 Sport Storm Gray



### Key Specifications

**114**  
HP

**64"**  
WIDTH

**14"**  
GROUND CLEARANCE

## ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	ProStar 1000 4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	114 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

## DIMENSIONS

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	1805 lbs (819 kg)
Fuel Capacity	9.5 gal (36 L)
Ground Clearance	14 in (35.6 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	146.9 x 64 x 72.8 in (373.1 x 162.6 x 184.9 cm)
Payload Capacity	900 lb (408 kg)
Wheelbase	117 in (297.2 cm)

## BRAKES

Front/Rear Brakes	
-------------------	--

	4-Wheel Hydraulic Disc with Dual-Bore Front and Single-Bore Rear Calipers
<b>Parking Brake</b>	Park In-Transmission

## ADDITIONAL SPECIFICATIONS

<b>Audio</b>	Not Equipped, Accessory Options Available
<b>Cargo System</b>	Lock & Ride®
<b>Doors</b>	Front & Rear Full Doors
<b>Electronic Power Steering</b>	Standard with Quick Turn Rack
<b>Hitch Type</b>	Not Equipped
<b>Instrumentation</b>	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
<b>Lighting</b>	LED Head Lights & Tail Lights Illuminated In-Cab Controls
<b>Other Standard Features</b>	Color Matched Seats Programmable Speed Limiting PIN Enabled Engine Start Security 660-W Charging System @ 3,000 RPM 6-Position PULSE Bar Front Tow Loop Front Bumper Passenger Grab Handle with Integrated Lug Nut Hex Wrench Driver and Passenger Dash Storage Bins
<b>RIDE COMMAND+</b>	Available as Accessory
<b>Seat Type</b>	Bolstered Bucket Seats with Driver & Passenger Seat Slider Retractable 3-Point Seat Belts 2nd Row Stadium-Raised Seating

## TIRES / WHEELS

<b>Front Tires</b>	29 x 9-14; Radial Tire
<b>Rear Tires</b>	29 x 11-14; Radial Tire
<b>Tilt Steering</b>	Standard Tilt
<b>Wheels</b>	Cast Aluminum

## SUSPENSION

<b>Electronic Suspension Control System</b>	Not Equipped
<b>Front Shocks</b>	2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
<b>Front Suspension</b>	Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 16 in (40.6 cm) of Wheel Travel
<b>Rear Shocks</b>	2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
<b>Rear Suspension</b>	Trailing Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel