

# 2025 RZR Pro R 4 Ultimate Super Graphite



## Key Specifications

**225**  
HP

**74"**  
WIDTH

**16"**  
CLEARANCE

## ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	1997cc
Drive System Type	Pro Performance True 2WD/4WD/4WD Lock
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Inline Four Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	225 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

## DIMENSIONS

Bed Box Dimensions (L x W x H)	29.5 x 23.8 x 8.1 in (75 x 60.5 x 20.6 cm)
Box Capacity	300 lb (136.1 kg)
Estimated Dry Weight	2,578 lbs (1169 kg)
Fuel Capacity	12.30 gal (46.56 L)
Ground Clearance	16 in (40.6 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	165.5 x 74 x 76.5" (420 x 188 x 194 cm)
Payload Capacity	900 lb (408 kg)
Person Capacity	4
Wheelbase	133.5 in (339.1cm)

## BRAKES

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor
<b>Parking Brake</b>	Park In-Transmission

## ADDITIONAL SPECIFICATIONS

<b>Audio</b>	Factory Tuned & Integrated Rockford Fosgate Stage 4 Audio System with RIDE COMMAND Source Unit. Includes (2) 100 watt 1-inch tweeters, (2) 100 watt 6.5-inch component front speakers, (2) 100 watt 6.5-inch coaxial rear speakers, (1) 400 watt 4-channel amplifier, and (1) 10-inch subwoofer with an integrated 400 watt subwoofer amplifier. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.
<b>Cargo System</b>	Lock & Ride®; Convertible Fold Flat Rear Seat Storage with Integrated Tie Down Points, 27.7 x 52.8 x 19.5 in (70.4 x 134.1 x 49.53 cm) Factory Equipped Cargo Liner
<b>Charging System</b>	High Output 1700w charging system @ 3,000 RPM
<b>Doors</b>	Front & Rear Full Doors
<b>Electronic Power Steering</b>	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and RIDE COMMAND Push Button Controls
<b>Hitch Type</b>	Not Equipped
<b>Instrumentation</b>	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio (Accessory Speakers Required - Sold Separately), In-Vehicle Communications Capable With Optional Sena Headsets, Polaris P.A.S.S Anti-Theft System. Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
<b>Lighting</b>	Signature Animated RZR Fang Accent Lighting White LED, Low / High & Red LED Tail / Brake Lights and Interior Accent Lighting
<b>Seat Type</b>	Front: Heated & Vented Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat sliders with tilt adjustability) and Retractable Click-6 Harnesses Rear: Stadium style seating with non-retractable 6-point harnesses

## TIRES / WHEELS

<b>Front Tires</b>	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
<b>Rear Tires</b>	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7

**Wheels**

5-Lug, 15" Cast Aluminum Rim with Painted Beadlock

## SUSPENSION

<b>Electronic Suspension Control System</b>	Polaris Dynamix DV 3.0 (Dual Valve Control) Semi-Active Compression and Rebound Damping System with Selectable Ride Modes: Comfort, Rock, Track, Baja
<b>Front Shocks</b>	FOX® 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
<b>Front Suspension</b>	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 27.0 in (68.6 cm) *Usable Travel, 22.25 in (56.5 cm) Wheel Travel, Unitized Hubs
<b>Rear Shocks</b>	FOX® 3.0 Live Valve X2 Internal Bypass (Electronically Controlled Compression and Rebound)
<b>Rear Suspension</b>	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 Piece Stabilizer Bar and 29.0 in (73.7 cm) *Usable Travel, 24.5 in (62.2 cm) Wheel Travel, Unitized Hubs