2025 RZR Pro S 4 Sport Storm Gray



Key Specifications

181 74" 28" HP STANCE TRAVEL

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	925cc
Drive System Type	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged
Fuel System/Battery	Electric Fuel Injection
Horsepower	181 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	2,268 lbs (1,029 kg)
Fuel Capacity	12 gal (45.4 L)
Ground Clearance	16"(40.6 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	157 x 74 x 77 in (399 x 188 x 196 cm)
Payload Capacity	1160 lbs. (526 kg)
Wheelbase	125 in (317.5 cm)

BRAKES

Front/Rear Brakes

Parking Brake	Park In-Transmission
	Calipers; Aluminum Top Hat Rotor
	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear

ADDITIONAL SPECIFICATIONS

Not Equipped, Accessory Options Available
Lock & Ride
High Output 900w charging system @ 3,000 RPM
Front & Rear Full Doors
Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel; RIDE COMMAND Push Button Controls
Not Equipped
Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet, Polaris P.A.S.S Anti-Theft System
Signature White LED Low/High Beam Headlights, Red LED Tail / Brake Lights, Interior Footwell Lights
Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Sub-Zero 4-Point Harnesses

TIRES / WHEELS

Front Tires	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Rear Tires	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Wheels	15" Cast Aluminum Rim with 5-Lug Pattern

SUSPENSION

Electronic Suspension Control System	Not Equipped
Front Shocks	Walker Evans® 2.5" Velocity Needle Shock with 16-Position Adjustable Clickers
Front Suspension	Light Weight Boxed Dual A-Arm with 3 Piece Stabilizer Bar and 27" (68.6 cm) Usable Travel, 22.25" (56.5 cm) Wheel Travel, Unitized Hubs
Rear Shocks	Walker Evans® 3.0" Velocity Needle Shock with 16-Position Adjustable Clickers
Rear Suspension	Tubular Trailing Arm with Boxed Gusseting and Toe Link, and Stabilizer Bar and 28.3 in (71.9 cm) *Usable Travel, 22.4 in (56.9 cm) Wheel Travel, Unitized Hubs