2025 RZR Pro XP 4 Ultimate Moss Green



Key Specifications

181

64" WIDTH

14.5"
GROUND CLEARANCE

ENGINE & DRIVETRAIN

| Cooling | Liquid |
|-----------------------------|--|
| Cylinders Displacement | 925cc |
| Drive System Type | Isolated Xtreme Performance True On-Demand AWD/2WD |
| Engine Braking System (EBS) | Not Equipped |
| Engine Type | 4-Stroke DOHC Twin Cylinder Turbocharged |
| Fuel System/Battery | Electronic Fuel Injection |
| Horsepower | 181 HP |
| Transmission/Final Drive | Automatic PVT P/R/N/L/H |

DIMENSIONS

| Bed Box Dimensions (L x W x H) | 26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm) |
|----------------------------------|---|
| Box Capacity | 300 lb (136 kg) |
| Estimated Dry Weight | 2,218 lbs (1006 kg) |
| Fuel Capacity | 13 gal (49.2 L) |
| Ground Clearance | 14.5 in (36.8 cm) |
| Hitch Towing Rating | N/A |
| Overall Vehicle Size (L x W x H) | 155 x 64 x 73.6 in (393.7 x 162.6 x 186.9 cm) |
| Payload Capacity | 900 lb (408.2 kg) |
| Person Capacity | 4 |
| Wheelbase | 125 in (317.5 cm) |
| | |

BRAKES

| Front/Rear Brakes | 4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers |
|-------------------|---|
| Parking Brake | Park In-Transmission |

ADDITIONAL SPECIFICATIONS

| Audio | Factory Tuned & Integrated Rockford Fosgate Stage 4 Audio System with RIDE COMMAND Source Unit. Includes (2) 100 watt 1-inch tweeters, (2) 100 watt 6.5-inch component front speakers, (2) 100 watt 6.5-inch coaxial rear speakers, (1) 400 watt 4-channel amplifier, and (1) 10-inch subwoofer with an integrated 400 watt subwoofer amplifier. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements. |
|---------------------------|---|
| Cargo System | Lock & Ride $^\circ$ Fold Flat Rear Storage, convertible rear seat storage with integrated tie down points, 27.7 x 52.8 x 19.5 in (70.4 x 134.1 x 49.53 cm) |
| Charging System | High Output 900w charging system @ 3,000 RPM |
| Doors | Front & Rear Full Doors |
| Electronic Power Steering | High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX and RIDE COMMAND Push Button Controls |
| Hitch Type | Not Equipped |
| Instrumentation | RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio (Accessory Speakers Required - Sold Separately), In-Vehicle Communications Capable With Optional Sena Headsets, Polaris P.A.S.S Anti-Theft System. Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet |
| Lighting | Signature Animated RZR Fang Accent Lighting White LED, Low / High & Red LED Tail / Brake Lights; Interior Accent Lighting |
| Seat Type | Bolstered Bucket Seats with 4-Way Adjustability (Including 6 in Front to Back Toolless Seat Slider with Tilt Adjustability) and Sub-Zero 4 Point Harness |

TIRES / WHEELS

| Front Tires | 30 x 10-14; 8-Ply Wheel Size 14 x 6 |
|-------------|-------------------------------------|
| Rear Tires | 30 x 10-14; 8-Ply Wheel Size 14 x 7 |
| Wheels | 14" Cast Aluminum |

SUSPENSION

| Electronic Suspension Control System | Polaris DYNAMIX 2.0 Semi-Active Compression Damping Suspension System |
|--------------------------------------|--|
| Front Shocks | FOX® 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping) |
| Front Suspension | High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) *Usable Travel, 17 in (43.2 cm) Wheel Travel |
| Rear Shocks | FOX® 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping) |
| Rear Suspension | Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) *Usable Travel, 20 in (50.8 cm) Wheel Travel |