2025 RZR Pro XP 4 Ultimate Moss Green



Key Specifications

181

64" WIDTH

14.5"

GROUND CLEARANCE

ENGINE & DRIVETRAIN

,
Liquid
925cc
Isolated Xtreme Performance True On-Demand AWD/2WD
Not Equipped
4-Stroke DOHC Twin Cylinder Turbocharged
Electronic Fuel Injection
181 HP
Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	2,218 lbs (1006 kg)
Fuel Capacity	13 gal (49.2 L)
Ground Clearance	14.5 in (36.8 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	155 x 64 x 73.6 in (393.7 x 162.6 x 186.9 cm)
Payload Capacity	900 lb (408.2 kg)
Person Capacity	4
Wheelbase	125 in (317.5 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Audio	Factory Tuned & Integrated Rockford Fosgate Stage 4 Audio System with RIDE COMMAND Source Unit. Includes (2) 100 watt 1-inch tweeters, (2) 100 watt 6.5-inch component front speakers, (2) 100 watt 6.5-inch coaxial rear speakers, (1) 400 watt 4-channel amplifier, and (1) 10-inch subwoofer with an integrated 400 watt subwoofer amplifier. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.
Cargo System	Lock & Ride $^\circ$ Fold Flat Rear Storage, convertible rear seat storage with integrated tie down points, 27.7 x 52.8 x 19.5 in (70.4 x 134.1 x 49.53 cm)
Charging System	High Output 900w charging system @ 3,000 RPM
Doors	Front & Rear Full Doors
Electronic Power Steering	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX and RIDE COMMAND Push Button Controls
Hitch Type	Not Equipped
Instrumentation	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio (Accessory Speakers Required - Sold Separately), In-Vehicle Communications Capable With Optional Sena Headsets, Polaris P.A.S.S Anti-Theft System. Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	Signature Animated RZR Fang Accent Lighting White LED, Low / High & Red LED Tail / Brake Lights; Interior Accent Lighting
Seat Type	Bolstered Bucket Seats with 4-Way Adjustability (Including 6 in Front to Back Toolless Seat Slider with Tilt Adjustability) and Sub-Zero 4 Point Harness

TIRES / WHEELS

Front Tires	30 x 10-14; 8-Ply Wheel Size 14 x 6
Rear Tires	30 x 10-14; 8-Ply Wheel Size 14 x 7
Wheels	14" Cast Aluminum

SUSPENSION

Electronic Suspension Control System	Polaris DYNAMIX 2.0 Semi-Active Compression Damping Suspension System
Front Shocks	FOX® 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)
Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) *Usable Travel, 17 in (43.2 cm) Wheel Travel
Rear Shocks	FOX® 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)
Rear Suspension	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) *Usable Travel, 20 in (50.8 cm) Wheel Travel