

RANGER XP Kinetic Premium Polaris Pursuit Camo



Key Specifications

110	3	14"
HP	PERSON CAPACITY	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Battery System	Lithium Ion, 14.9 kWh Nominal
Cooling	Active Air and Liquid
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Regenerative Braking
Horsepower	110 HP
Motor Type	Internal Permanent Magnet AC Motor
Torque	140 LB-FT
Transmission/Final Drive	Gates Synchronous Belt H/L/N/P (Electronic Forward/Reverse), Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,754 lbs. (796 kg)
Ground Clearance	14" (35.6 cm)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 78 in (305 x 158 x 198 cm)
Payload Capacity	1,500 lbs (680.4 kg)
Person Capacity	3
Wheelbase	81 in (206 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park In-Transmission

TECHNOLOGY

Adjustable Driver Seat	Standard
Cargo System	Lock & Ride®
Charging Kit Included (EVSE)	J1772, Combined Level 1 / Level 2 Mobile
Color / Graphics	Polaris Pursuit Camo
Electronic Power Steering	Standard
Estimated Range	45 Miles
Instrumentation	Driver's Side Dual-sweep Analog Dials w/ 4" Multi-Color LCD Rider Information Center: Power Use and Regen %, Battery State of Charge %, Range Remaining, Charging Rate, Battery Temperature, Motor Temperature, Accessory Voltage, Speedometer, Odometer, Tripmeter, Gear Indicator, Service Indicator and Codes, Programmable Service Intervals, Seat Belt Reminder, User Selectable Backlighting & Brightness, Clock
Lighting	Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps
Onboard Battery Charger	3 kW
Other Standard Features	Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Premium Steering Wheel and Interior Accents, Polaris Pulse Electrical System (6 position), DC Outlets, Dual USB Port, Cargo Box Located 12V SAE Port with In-Dash On/Off Switch. *Connectivity with Ride Command + App
RIDE COMMAND+	Factory-Installed
Tilt Steering	Standard

WHEELS & TIRES

Front Tires	29 x 9-14; PRO ARMOR X-TERRAIN
Rear Tires	29 x 11-14; PRO ARMOR X-TERRAIN
Tire Ply Rating	8 Ply Rated
Wheels	14 in. (35.6 cm) Aluminum

SUSPENSION

Front Suspension	Dual A-Arm, 10 in (25.4 cm)
Rear Suspension	Dual A-Arm, IRS 10" (25.4 cm) Travel
Turning Radius	13.3 ft (406.4 cm)

