

RANGER 500 Sage Green



Key Specifications

28	58.5"	10"
HP	WIDTH	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	567 cc
Drive System Type	All-wheel drive with auto-locking front drive and selectable VersaTrac Turf Mode
Engine Type	4-stroke single cylinder DOHC
Fuel System/Battery	Electronic fuel injection
Horsepower	28
Transmission/Final Drive	Automatic PVT H/L/N/R/P; shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	32.6 x 46.2 x 11.25" (82.7 x 117.3 x 28.6 cm)
Box Capacity	300 lbs. (136.1 kg)
Curb Weight	1,210 lbs. (549 kg)
Estimated Dry Weight	1,155 lbs. (524 kg)
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	10" (25.4 cm)
Hitch Type	Standard 2" (5 cm) receiver
Overall Vehicle Size (L x W x H)	110 x 58.5 x 74.8" (279.4 x 148.6 x 190 cm)
Payload Capacity	1,000 lbs. (454 kg)
Person Capacity	2
Towing Capacity	1,500 lbs. (680 kg)
Turning Radius	13.5 ft (4.2 m)

Wheelbase	73.2" (186 cm)
-----------	----------------

BRAKES

Front/Rear Brakes	4-wheel hydraulic disc
Parking Brake	Park in-transmission

WHEELS & TIRES

Front Tires	25 x 8-12; Carlstar 489
Rear Tires	25 x 10-12; Carlstar 489
Wheels	12" aluminum

SUSPENSION

Front Suspension	MacPherson strut 9" (22.9 cm) travel
Rear Suspension	Dual A-arm, IRS 10" (25.4 cm) travel

EXTERIOR FEATURES

Cargo System	Gas-assist dump box with Lock & Ride accessory integration
Door Type	Cab nets
Vehicle Protection	Steel front bumper with integrated winch mount
Winch	2,500-lb. winch with wired remote

LIGHTING & ELECTRICAL

Electrical System	DC outlet, 660-W stator charging system
Lighting	LED headlights and taillights

COMFORT & CONVENIENCE

Cab Components	Roof
Driver Instrumentation	4" LCD rider information center: user-selectable blue/red backlighting and brightness, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder
Seat Type	2-person, flip-up bench seat with 3-point harness.
Speed Limiting	Speed limiting controlled in gauge
Steering	Tilt adjustment