

RZR Pro XP Ultimate Earth Blue



Key Specifications

181	64"	14.5"
HP	WIDTH	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	925 cc
Drive System Type	Isolated Xtreme Performance true on-demand AWD/2WD
Driveline Features	Not equipped
Engine Type	4-stroke DOHC twin-cylinder turbocharged
Fuel System/Battery	Electronic fuel injection
Horsepower	181
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)
Box Capacity	300 lbs. (136.1 kg)
Curb Weight	1,753 lbs. (795kg) CA 1,760 lbs. (798 kg)
Estimated Dry Weight	1,665 lbs. (755 kg) CA 1,672 lbs. (758 kg)
Fuel Capacity	12 gal. (45.4 L)
Ground Clearance	14.5" (36.8 cm)
Hitch Type	Not Equipped
Overall Vehicle Size (L x W x H)	126.1 x 64 x 71.7" (320 x 163 x 182 cm)
Payload Capacity	740 lbs. (335.7 kg)
Person Capacity	2
Towing Capacity	N/A
Wheelbase	96" (244 cm)

BRAKES

Front/Rear Brakes	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor
Parking Brake	Park in-transmission

TECHNOLOGY

Audio System	Factory-tuned and integrated Rockford Fosgate Stage 4 audio system with RIDE COMMAND source unit. Includes: (2) 100-W 1" tweeters, (2) 100-W 6.5" component front speakers, (2) 100-W 6.5" coaxial rear speakers, (1) 400-W 4-channel amplifier, and (1) 10" subwoofer with an integrated 400-W subwoofer amplifier. *Audio system is IPX7- and IPX9K-water immersion tested to withstand the wet elements.
Connected Vehicle Services	Not equipped, accessory options available
Rear Camera	Equipped
Security	Polaris P.A.S.S. anti-theft system
Touch Screen Display	7" Display, powered by RIDE COMMAND, featuring: DYNAMIX 2.0 visualizer, built-in GPS, Group Ride (cell-based or GPS-based), topographic mapping, Bluetooth & USB smartphone connectivity, AM/FM & weather radio (accessory speakers required - sold separately), in-vehicle communications capable with optional Sena headsets

WHEELS & TIRES

Front Tires	30 x 10-14; wheel size 14 x 6"
Rear Tires	30 x 10-14; wheel size 14 x 7"
Tire Ply Rating	8-ply
Wheels	14" cast aluminum rim with 4-lug pattern

SUSPENSION

Electronic Suspension Control System	Polaris DYNAMIX 2.0 semi-active compression damping suspension system with selectable ride modes: Comfort, Sport, Firm
Front Shocks	FOX 2.5" Podium Live Valve with bottom-out control (electronically controlled damping)
Front Suspension	High-clearance dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel, 17" (43.2 cm) wheel travel*
Rear Shocks	FOX 2.5" Podium Live Valve with bottom-out control (electronically controlled damping)
Rear Suspension	Trailing arm and high-clearance radius rods with stabilizer bar and 22" (55.9 cm) usable travel, 20" (50.8 cm) wheel travel*

EXTERIOR FEATURES

Cargo System	Lock & Ride
Door Type	Half doors
Vehicle Protection	Bull bumper
Winch	Not equipped

LIGHTING & ELECTRICAL

Electrical System	High-output 900-W charging system @ 3,000 RPM
Lighting	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.

COMFORT & CONVENIENCE

Cab Components	Half doors, poly roof
Drive Modes	Not equipped
Driver Instrumentation	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system
Electronic Power Steering	High-assist electronic power steering with quick-turn rack
Heat and/or Air Conditioning	Not equipped
Ride Control	Not equipped
Seat Type	Bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider with tilt adjustability) and passenger tilt adjustability; Sub-Zero 4-point harness.
Speed Limiting	Not equipped
Steering	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.